

Desktop Dual-sided Card Printer



S28



Front



Top



Back

SEAORY S

Lightweight Body, Reliable Quality

Adopt thermal dye-sublimation printing technology with high definition
With better card-printing capability continuously, saving-time effort
Simple operation interface and easy to use
Lightweight body and easy to maintain
Low noise in printing process
High printing speed engine

Features

Automatic dual-sided printing
Support manual feeding by back end
Support sensor alarm for no card and defective-card slot

Consumables

Full panel YMCKO ribbon: 100 prints/roll, 300 prints/roll
Full panel YMCKOK ribbon: 240 prints/roll
1/2 panel YMCKOKO ribbon: 250 prints/roll
1/2 panel YMCKO ribbon: 450 prints/roll
Black ribbon: 100mx60mm, 200mx60mm monochrome
Monochrome ribbon (gold/silver/white/red/ blue): 100mx60mm
KO ribbon: 500 prints/roll
Anti-counterfeit invisible UV ribbon: 100mx60mm

Optional Multi-function modules Support various card printing

Dual interface chip card encoding module
Contactless ID card encoding module
UHF chip card encoding module
Magnetic stripe card encoding module



With high definition photo effect which
printed by Dye sublimation technology



Come with professional printing software

Technical Parameter

Model	S28 / Desktop Dual-sided Card Printer
Specifications	383 × 174 × 208 (mm), 4.6Kg without output hopper
Interfaces	USB2.0 & Ethernet
Input Capacity	100 cards
Output Capacity	50 cards
Print Speed	Monochrome printing: 3~5 s per card(single-sided) / 7~9 s per card(dual-sided); Full-color(YMCKO) printing: 18 s per card(single-sided) / 37 s per card(dual-sided).
Card Material	PVC / Composite PVC
Power	AC 100~240V, 50/60 Hz, DC 24-25.5V, 2.7 A
Print Dimension	ISO CR80 (53.98mm×85.60mm), edge-to-edge printing
Print Resolution	300dpi × 300dpi, 300dpi × 600dpi, 300dpi × 1200dpi
Memory	128MB
Print Method	Dye sublimation (Direct-to-Card)
Card Thickness	0.3-1.05mm
LCM Display	Chinese: 8 characters per line, 2 lines / English: 16 characters per line, 4 lines / Multi-language
Operation System	Driver: Support Windows XP/7/8/10/11, Windows Server 2003/2008/2012/2016, Linux, and NeoKylin, Kylin, UOS and other Made-in-China operating systems. SDK: Support Windows XP/7/8/10/11, Windows Server 2003/2008/2012/2016, Linux, and NeoKylin, Kylin, UOS and other Made-in-China operating systems Card Design Software: iCARDE card design software, support Windows XP/7/8/10/11 operating systems
Warranty	Card printer: 24 months (artificial damage excluded) / Print head: Replace one for free within 1 year (artificial damage excluded)
Operating Condition	1. Regular running temp.: 15°C-30°C(59-86°F), 20%~65% RH non-condensing 2. Lowest / Highest running temp.: 0°C(32°F) / 40°C(104°F), 20%~65% RH non-condensing
Storage Condition	Temp.: -5°C-70°C(23-158°F), 20%~70% RH non-condensing
Certificates	CCC, FCC, CE, ROHS, UKCA

