

**Compuprint**

**SP-40**

**PASSBOOK PRINTER**

Dedicated printing solution for front office application



## Value and Features

Reliable, Fast and Powerful

Compact, elegant,  
contemporary design

Secure document handling  
with fast transaction time

User-Friendly

Fully compatible with today's  
standard and financial application

Powerful system to support  
future application and system  
migration



**SOLID BUSINESS MACHINES CENTER, INC.**

SUITE 303, SINGSON BUILDING, PLAZA MORAGA, BINONDO, MANILA, PHILIPPINES 1006

Trunkline: (632) 242-1111 Connecting all Departments Fax No.: (632) 242-1345, 242-1348

e-mail: [solidmac@pltdsl.net](mailto:solidmac@pltdsl.net)

**[www.solidmac.com.ph](http://www.solidmac.com.ph)**



## TECHNICAL SPECIFICATION

Print Head	• 24 pin DOT Matrix Impact Printer
Resolution	• 360 x 360 dpi (HxV)
Line Length	• 94 column (cut sheet) @ 10cpi
Printing Speed	• 400 cps @ 10 cpi (draft) / 133 cps @ 10 cpi (LQ)
Pitch	• 10, 12 and cpi
Max. Thickness	• 2.2 mm
Emulation	• 4.1 inches Graphic LCD
Counterfeit Detection	• IBM Personal Printer 2390+, Proprinter XL24AGM, IBM 4722, 9068, Epson 570 and Olivetti PR40+, PR2, 2845, Epson LQ, Oki 5330/5630
Resident Fonts	• Draft, Courier, Gothic, Prestige, Presentor, Script, OCR-A, OCR-B, Boldface
Barcodes	• UPC/A, UPC/E, EAN8, EAN13, Code 39, Code 128 Postnet, Codabar, DD-ON 2, ADD-ON 5, Code 11, Code 93, BCDm MSI, 2/5 Interleaved, 2/5 Matrix, 2/5 Industrial
Interfaces	• Parallel, IEEE 1284 bidirectional, Serial RS-232/C, USB 2.0, Automatic Interface Switching
Memory	• 64 Kbytes buffer
Special Function	• Automatic Gap Adjustment (AGA), Auto Alignment, Auto Border Recognition
Ribbon Life	• 15 million character (black)
Reliability	• MTBF: 10,000 hours
Print Head Life	• 400 million characters per pin
Physical Dimensions & Weight	• 400(W) x 200(H) x 295(D)mm
Power Supply	• Tension: 88~264V; Frequency: 47~63HZ; Consumption: 120W max (Printing). 10W (Standby)
Environmental Conditions	• Temp.: working 5/40°C, stock-25/60° C, Humidity: working from 20-85% (r.h); stock from 10-90% (r.h)
Standard	• EN 60950, IEC 950
Environment	• Energy star compliant
Noise Level	• 54 dbA

The Compuprint SP-40 is designed to be the ultimate printing solution for transactional application and financial services. By assuring process efficiency and offering a competitive low cost of ownership, the Compuprint SP-40 is the ideal, long-term asset for business and financial institution.

## FEATURES

### A leading-edge serie for today and tomorrow

- The Compuprint SP-40 transactional printer integrates state-of-the-art Compuprint technology and innovation that's based on more than 30 years of leadership in serial dot matrix printer technology. It's built on unsurpassed technologies to offer the most efficient transactional device available on the market. It supports all critical application needs in business and financial environment.

### Fast, Flexible, Reliable

- The SP-40 prints document quickly, clearly and securely. Its ergonomic desing and features offer a unique, easy handling of documents at the front desk, allowing users total dedication to their customers.

### For a broad range of intensive printing requirements

- Equipped with the most flexible and powerful electronic available today, the SP-40 represents the ideal platform for institution and application developers. It supports all of today's industry-standard applications. It's open platform electronic is ready to support all of the future application or system migrations.

## ORDERING INFORMATION

### Printers and Supplies

Compuprint SP-40	PRT0520
6 black ribbons 5 MC	PRK5287-6
6 black ribbon 15 MC	PRK5290-6
<b>Special Versions</b>	
Compuprint SP-40 Display	PRT0526
Compuprint SP-40 LAN	PRT0519-LAN
Compuprint SP-40 dual serial I/F	PRT0528
Compuprint SP-40 MSR/W	PRT0529
Compuprint SP-40 MSR/W & MICR	PRT0530
Compuprint SP-40 dual scanner	PRT0531
Compuprint SP-40 dual scanner-MSR/W & MICR	PRT0532
Compuprint SP-40 dual scanner-MSR/W	PRT0533
Compuprint SP-40 Passport	PRT0550
Compuprint SP-40 barcode reader	PRT0519-BCR