



SC-303



SC-313



SC-360

SPECIFICATIONS	SC-303	SC-313	SC-360
Countable Speed	< 2,700 coins/min.	< 2,700 coins/min.	up to 3,000 coins/min.
Diameter Range	14-34 mm/0.55-1.30"	14-34 mm/0.55-1.30"	18-38 mm
Thickness Range	1.0-3.4 mm/0.04-0.13"	1.0-3.4 mm/0.04-0.13"	None
Coin Hopper Capacity	None	3,000 coins (3 litres)	6,000 coins (6 liters)
Voltage	100-130/220-240 V, 60/50 Hz	100-130/220-240 V, 60/50 Hz	110/230 V, 60/50 Hz
Power	40 W	55 W	120 W
Dimensions	370(L) x 220(W) x 165(H) mm	370(L) x 260(W) x 315(H) mm	480(L) x 295(W) x 380(H) mm
Weight	8.4 kg/18.5 lbs	11.6 kg/25.6 lbs	19.5 kg/43.0 lbs
Features	• Non-volatile memory • Batch stops 5-10,999 • Automatic reverse • Automatic stop • Easy-to-read LED display • Portable • Universal settings • High capacity	• Non-volatile memory • Batch stops 5-10,999 • Automatic reverse • Automatic stop • Easy-to-read LED display • Universal settings • High capacity	• Large Hopper • Automatic Hopper with filling • Automatic Reverse • Automatic Stop • Pre-selectable bag stop • Memory • High Capacity
Accessories	• CA 1 Coin Adapter, for accessories marked (A) • IH 1 Insert Holder (A) • TI 1 Tubing Inserts for prefabricated coin tubes (A) • BGS 1 Bag Guide with Shelf (A) • BG 1 Bag Guide without shelf (A) • BA 3 Bagging Attachment for rejected coins	• CA 1 Coin Adapter, for accessories marked (A) • IH 1 Insert Holder (A) • TI 1 Tubing Inserts for prefabricated coin tubes (A) • BGS 1 Bag Guide with Shelf (A) • BG 1 Bag Guide without shelf (A) • BA 3 Bagging Attachment for rejected coins	• BA 5 Bagging attachment (for the rejected coins) • RD 8 Remote display • IH 1 Insert Holder (A) • TI 1 Tubing Inserts for prefabricated tubes (A) • BGS 1 Bag Guide with Shelf (A) • BG 1 Bag Guide without shelf (A) • FC 3 Foot-control



SOLID BUSINESS MACHINES CENTER, INC.

SUITE 303, SINGSON BUILDING, PLAZA MORAGA, BINONDO, MANILA, PHILIPPINES 1006

Trunkline: (632) 8242-1111 Connecting all Departments Fax No.: (632) 8242-1345, 8242-1348

e-mail: sales@solidmac.com.ph

www.solidmac.com.ph